AD A-10555/

MEMORANDUM REPORT ARBRL-MR-03136

TRAJECTORY PREDICTIONS FOR A 75 MM SOLID FUEL RAMJET TUBULAR PROJECTILE

Carl W. Nelson

September 1981



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND BALLISTIC RESEARCH LABORATORY ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

Destroy this report when it is no longer needed. Do not return it to the originator.

Secondary distribution of this report by originating or sponsoring activity is prohibited.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22151.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of traile names or manufacturers' names in this report does not constitute indorsement of any commercial product.

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION I	PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
MEMORANDUM REPORT ARBRL-MR-03136		
4. TITLE (and Subtitle)	<u> </u>	5. TYPE OF REPORT & PERIOD COVERED
TRAJECTORY PREDICTIONS FOR A 75 MM S RAMJET TUBULAR PROJECTILE	SOLID FUEL	BRL Memorandum Report
KAMBET TOBOLAR PROJECTILE		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(a)		8. CONTRACT OR GRANT NUMBER(8)
CARL W. NELSON		
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Armament Research & Developm US Army Ballistic Research Laboraton ATTN: DRDAR-BLI	ment Command ry	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Aberdeen Proving Ground, MD 21005 11. CONTROLLING OFFICE NAME AND ADDRESS		1L161101A91A
US Army Armament Research & Developm	ment Command	12. REPORT DATE
US Army Ballistic Research Laborator	ry	SEPTEMBER 1981
ATTN: DRDAR-BL		28
Aberdeen Proving Ground MD 21005 14. MONITORING AGENCY NAME & ADDRESS(If different	from Controlling Office)	15. SECURITY CLASS. (of this report)
-		UNCLASSIFIED
*		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
Approved for public release; distrib	oution unlimited	
17. DISTRIBUTION STATEMENT (of the abetract entered t	in Block 20, if different from	m Report)
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse aide if necessary and Solid Fuel Ramjet	d identify by block number)	
Tubular Projectile		
Air Breathing Combustion		
Trajectory		
Guns		
20. ABSTRACT (Continue on reverse side if necessary and The AFAPL ramjet design analysi trajectory for a 75 mm solid fuel ra	s code was modif	
velocity was found sensitive to the		
•		

TABLE OF CONTENTS

	Pag	е
	LIST OF ILLUSTRATIONS	
Ι.	INTRODUCTION	
II.	ASSUMPTIONS	
III.	FUEL DATA	
IV.	COMBUSTION	
ν.	RESULTS	
	REFERENCES	
	LIST OF SYMBOLS	
	APPENDIX A	
	DISTRIBUTION LIST	

LIST OF ILLUSTRATIONS

Figure			Page
1.	Fuel-in-Cowl Schematic		10
2.	Comparison of Correlated and Measured Combustion Efficiency		12
3.	Non-Linear Fitting Function for Combustion Efficiency		12
4.	Velocity vs Range for 75 mm SFRJ-TP		13
5.	Combustion Chamber Performance of 75 mm SFRJ-TP		14
6.	Effect of Combustion Efficiency Correlation on Predicted Efficiency		14

I. INTRODUCTION

Army interest in Solid Fuel Ramjets (SFRJ) spawned a technology demonstration program for a gun launched tubular projectile with an SFRJ combustion chamber. Chemical Systems Division of United Technologies Corp designed a 75 mm demonstration round after wind tunnel and direct connect tests*. New flight regimes were encountered in the high velocity (Mach 4 plus) at sea level. Almost all ramjet experience has been with either low velocity or high altitude; performance correlations have not been developed for the tubular projectile flight regime. Data remain scarce on regression rate and combustion efficiency dependence on air flow conditions.

Predicting the performance of these SFRJ projectiles requires coupling the solid fuel combustion chamber to the supersonic diffuser inlet. An AFAPL (Air Force Aero Propulsion Laboratory) computer code¹ for ramjet design analysis was modified to compute combustion in the solid fuel chamber. Expected performance of the 75 mm SFRJ tubular projectiles is hereby reported.

II. ASSUMPTIONS

- 1. Enthalpy versus temperature and pressure for incoming air taken from Keenan and Kaye** properties of air at low pressure. The values were supplied with the AFAPL code. At the nominal launch velocity (Mach 4.29) on a standard day at sea level, the air stagnation temperature and pressure are 1260K and 24.9 MPa.
- 2. US Standard Atmosphere. For these sea level, standard day trajectories no altitude variations need be considered.
- 3. Constant drag coefficient (.0645). A value suggested by Chemical Systems Division after its preliminary design studies and some wind tunnel tests. That the coefficient will be velocity dependent has been conveniently ignored.
- 4. Constant nozzle efficiency (0.98). A reasonable value for conical nozzles. Variations due to chamber conditions and nozzle design have been ignored.
- 5. Normal shock inlet operation. Pressure loss ratios in the inlet calculated from standard normal shock tables for an ideal gas of 1.4 specific heat ratio. Exact inlet calculations are not made; only area ratios are considered.
- 6. Adiabatic processes. No heat loss to projectile body.
- 7. Combustion fully established as initial condition. Ignition transient not considered.

^{*}A direct connect test is a combustion chamber without inlet. Air enters the chamber at flow conditions expected at the inlet dump plane.

¹K. A. Watson, "Air breathing Missile Design Program-FJ", AFAPL-FJT-TM-77-29, AF Aero Propulsion Laboratory, (November 77).

^{**}Provided without reference citation.

III. FUEL DATA

Fuel thermodynamic data, supplied by Chemical Systems Division, are shown in Table 1. The values represent complete combustion at the air temperature and equivalence ratio. In the calculations final temerature is corrected for combustion efficiency in the standard method

$$T_f = T_a + \eta_c (T_{t_f} - T_a) ,$$

where $\eta_c = combustion efficiency,$

 $T_f = final temperature,$

 $T_a = incoming air temperature,$

 T_{t_f} = theoretical final temperature.

Specific heat ratio and molecular weight were assumed unaffected by combustion efficiency. The data are given only for one pressure (3.0 MPa). No corrections were attempted for pressure. (Nominal chamber pressure is near that level.)

IV. COMBUSTION

Flow of fuel from the solid surface into the combustion chamber is governed by the simple $\,$

$$\dot{w}_f = \rho_f \dot{r} S$$
.

Calculations of regression rate $(\mathring{\mathbf{r}})$ and surface area (s) provide the only challenge. Regression rate is available for a few fuels from CSD monthly contract reports in the form

$$\dot{r} = a G^n$$
,

where G is the air mass velocity and constants a and n can vary with air stagnation temperature and pressure. CSD's data for the fuel intended for the 75 mm demonstration rounds produces a regression rate correlation of

$$\dot{r} = 0.116 \quad G^{0.64}$$
 (1)

TABLE 1. FUEL THERMODYNAMIC DATA

 $P_4 = 440 \text{ psia}$

φ	0.306	0.394	0.499	0.604	0.700	0.796	0.901	1.00	
AIR TEMPERATURE(R)	(R)		FINAL T	TEMPERATURE (K)	(X)				
1300 1900 2500 3000	1465 1765 2060 2280	1645 1920 2220 2425	1860 2120 2380 2585	2060 2298 2550 2720	2225 2448 2675 2825	2380 2585 2775 2908	2528 2692 2755 2975	2605 2760 2902 3012	
			SPECIFIC	IC HEAT RATIO	CIO				
1300 1900 2500 3000	1.297 1.284 1.266 1.248	1.2875 1.272 1.254 1.236	1.2745 1.2575 1.240 1.222	1.2595 1.2425 1.220 1.1985	1.2435 1.226 1.199 1.1785	1.227 1.2045 1.178 1.162	1.203 1.177 1.1585 1.149	1.176 1.161 1.149 1.142	egenfrikke helig M edirinsk e kryssensk figurer und vertrikskelende var med
			Z IOM	MOI ECHII AB WEICHT					Allinois e artino e trono e trono anticolorio.
1300	20 10			20 25	o c				
1900	29.10								
2500 3000	29.10 29.05	29.10 29.05	29.15 29.15	29.22 29.15	29.17 29.05	29.07 28.92	28.95 28.75	28.75	se pe-
						****]

Exposed fuel surface is a straightforward geometry problem. All planned configurations for the gun a launched projectiles are internally perforated cylinders. (The high spin rate precludes the common form spoke gain of guided missile applications). Only one complication is presented - the grain length. The fuel-in-cowl design packs in more fuel but regression shortens the exposed length. Exact surface calculation depends on the specific internal cowl design but the goemetry adjustment is straightforward. Figure 1 shows a typical fuel-in-cowl design.




Figure 1. Fuel in Cowl Schematic

Combustion efficiency correlations are also available from CSD monthly contract reports for a few fuels. It is in the form

$$\eta = b \phi^{c} T_{a}^{d} \frac{A_{3}}{A_{i}}. \qquad (2)$$

The equivalence ratio ϕ comes from the fuel and air flow calculations and the step area ratio $\frac{A_3}{A_1}$ from the chamber geometry.

CSD's reported correlation 2 for the 75 mm fuel is

$$\eta = 0.22 \phi$$
 T_a
 T_a
 A_3
 A_i
 A_3
 A_i
(3)

Both regression rate and combustion efficiency change with time because air conditions change with projectile velocity and because the fuel regresses to increase the step area ratio ${\rm A_3/A_i}$.

²Monthly Progress Report No. 22, Chemical Systems Divisions, (August 80).

The combustion efficiency correlation was derived from tests where the efficiency never exceeded 0.90. Extrapolation to the combustion chamber conditions for the 75 mm projectile would predict efficiencies greater than 1.0. Maximum of 1.0 was assigned despite arguments³ for greater measured efficiencies.

Some recent CSD performance calculations for a 35 mm SFRJ-TP used an efficiency expression $\,$

$$\eta = \frac{0.18}{\phi^{-.45}} \quad \frac{A_3}{A_i} \qquad \frac{T_a}{1000} \qquad , \tag{4}$$

although no source was cited.

An independent analysis $_4$ of the reported CSD test data for fuel 21862 obtained a least squares fit $_4$ of

$$\eta = \frac{.232}{\phi^{-.347}} \frac{A_3}{A_i} \frac{.491}{\frac{T_a}{1000}} \frac{.944}{.}$$
 (5)

Figure 2 compares experimental with correlated values of efficiency for Eq. (5). Appendix A gives the data used in the analysis.

The transition from the linear correlation,

$$n = a X$$

where X is the power function of all the influencing variables to a limit of $\eta \rightarrow 1.0$ requires some imagination. The test data do not extend to those conditions. An arbitrary selection of a functional dependence must suffice. It should satisfy a few conditions: (1) for mid range (0.4<aX<0.8) it should be η = aX; (2) for aX<0.4 it is irrelevant in present applications, (3) it must approach η = 1 for aX<0.8 smoothly. Final forms are limited only by the imagination; physics provides few clues. After some acrobatics the following form makes a reasonable estimate

³R. Dunlap, G. E. Jensen, "Combustion Efficiency in a SFRJ at the Fuel Grain Exit Plan", 16th JANNAF Combustion Meeting, Monterey, CA (September 1979).

⁴R. H. Moore, R. K. Zeigler, "The Solution of the General Least Squares Problem with Special Reference to High Speed Computers" Los Alamos Scientific Laboratory Report LA2367 (March 1960).

$$\eta = 1 - \left[4 - \frac{1}{2} (X-3)^2\right] \quad Xe^{-1.1X} . \tag{6}$$

For a = 0.23 comparison of η with aX is shown in Figure 3.




Figure 2. Comparison of Correlated and Measured Combustion Efficiency 1.2




Figure 3. Non-linear fitting function for Combustion Efficiency

Regression rate was also obtained from a least square fit for fuel 21862. With air temperature dependence, the best fit is

The regression rates obtained with this fit are close to those obtained with the CSD reported dependence (Eq. (1)).

V. RESULTS

Trajectories were calculated for the 75 mm SFRJ-TP designed for gun firing demonstration. Figure 4 shows the velocity versus range on non-dimensional scales of velocity divided by initial velocity and range divided by range at burnout. Security classification precludes reporting actual velocities and ranges.




Figure 4. Velocity vs range for 75 mm SFR J-TP

The three trajectories in Figure 4 come from different assumptions on combustion efficiency. The central curve represents the amended least squares fit of Eq. (6); the upper curve represents the CSD offered efficiency of Eq. (3); the lower curve represents the CSD suggested Eq. (4).

The spread among the calculated trajectories demonstrates the sensitivity to the assumption of combustion efficiency. Since each represents an extrapolation from the test data from which the correlations were derived, they may all be wrong. Both the need for extrapolation and the sensitivity demonstrate the necessity for data in the expected conditions.

Some details of the combustion chamber performance are shown in Figure 5 which displays time history of regression rate and air mass velocity.





Figure 5. Chamber performance of 75 mm SFRJ-TP

Figure 6 shows the predicted combustion efficiency for various assumptions about its dependence on chamber conditions. Curve 30 uses the CSD Eq. (3); Curve 44 uses the amended fit Eq. (6); Curve 40 uses the re-analyzed CSD data correlation, Eq. (5); Curve 29 uses the CSD correlation of Eq. (4). All the calculations limited the efficiency to 1.0 arbitrarily.



t/tbo
Figure 6. Effect of Combustion Efficiency Correlation on Predicted Efficiency

REFERENCES

- 1. K. A. Watson, "Air breathing Missile Design Program-FJ", AFAPL-FJT-TM-77-29, AF Aero Propulsion Laboratory, (November 77).
- 2. Monthly Progress Report No. 22, Chemical Systems Divisions, (August 80).
- 3. R. Dunlap, G. E. Jensen, "Combustion Efficiency in a SFRJ at the Fuel Grain Exit Plan", 16th JANNAF Combustion Meeting, Monterey, CA (September 79).
- 4. R. H. Moore, R. K. Zeigler, "The Solution of the General Least Squares Problem with Special Reference to High Speed Computers" Los Alamos Scientific Laboratory Report LA2367 (March 1960).

LIST OF SYMBOLS

- G air mass velocity
- r fuel regression rate
- S Fuel surface area
- T_a Air Temperature (Stagnation)
- $^{\mathrm{T}}\mathrm{f}$ Final Combustion Temperature
- $T_{ t f}$ Theoretical Final Combustion Temperature
- W Mass flow rate
- $\mathbf{n}_{\mathbf{C}} \quad \text{Combustion efficiency}$
- φ Equivalence ratio
- ρ_f Fuel density

APPENDIX A

CSD TEST DATA

APPENDIX A

CSD TEST DATA

		A ₃					
Test	T _a	Ai	<u>P</u>	<u>G</u>	<u>φ</u>	regr rate	n
7060							<u>n</u>
7068	1285	2.017	116	.566	.543	.049	.576
7070	1845	2.334	204	.729	.580	.074	.753
7071	1860	2.354	271	.965	.539	.091	.786
7072	1860	2.334	250	.927	.876	.106	.627
7073 7074	1850	1.572	191	.826	.850	.087	.520
7074	1850	1.490	127	.573	.882	.061	.522
7075	2200	1.572	200	.807	.613	.081	.831
7078	2200	2.198	207	.768	.696	.090	.882
7078	2200	1.541	203	.814	.844	.084	.677
6939	2200 1850	1.715	155	.733	.717	.091	.822
6940	1850	1.399	319	1.120	.522	.090	.555
6941	1850	1.394	222	.780	.590	.071	.525
6942	1850	1.391	115	.390	.777	.048	.443
6943	1860	1.405	62	.200	1.069	.033	.447
6944	1850	1.333	269	1.000	.534	.080	.549
6945	1855	1.391	264	.980	.415	.083	.581
6946	1860	1.374	329	.990	.393	.079	.610
6947	1855	1.373 1.432	346 223	1.00	.524	.080	.574
6948	1850	1.432	207	.970	.598	.091	.587
6928	1840	1.419	234	.930	.489	.095	.586
6929	1885	1.419	234	.970	.409	.082	.649
6930	1885	1.410	239	1.00	.408	.084	.625
6931	1885	1.429	238	.980 .980	.433	.088	.580
6933	1910	1.464	244	.970	.432	.088	.581
6934	1880	1.478	247	.960	.574	.088	.489
6935	1850	1.401	323	1.14	.399	.091	.510
6936	1850	1.389	214	.780	. 442	.092 .070	.743
6937	1850	1.389	111	.400	.589	.048	.587
6938	1850	1.392	58	.200	.786	.032	.475 .382
6916	1850	1.359	236	1.0	.439	.032	.688
6917	1850	1.391	241	.99	.448	.000	.681
6918	1850	1.401	260	1.02	.586	.092	.624
6919	1850	1.463	267	1.00	.579	.091	.654
6921	1600	1.521	214	.86	.383	.070	.711
6922	2020	1.415	250	.98	.468	.094	.696
6923	2020	1.391	259	1.01	.576	.089	.612
6924	1850	1.409	289	.97	.401	.080	.683
6925	1850	1.392	302	.99	.532	.081	.632
6927	1840	1.030	234	.96	.427	.085	.630
6871	1870	1.589	254	1.40	.498	.113	.689
6872	2050	1.660	271	1.35	.576	.130	.702
6873	2050	1.543	194	1.03	.643	.106	.650
6874	2060	1.313	323	1.54	.564	.148	.733
6875	1850	1.224	180	1.02	.609	.098	.646
6876	1840	1.307	304	1.53	.543	.140	.707

APPENDIX A

CSD TEST DATA

		A ₃					
	т					regr	
Test	$\frac{T_a}{a}$	Ā	<u>P</u>	<u>G</u>	<u> </u>	rate	<u>n</u>
6877	1840	1.688	315	1.61	.508	.138	.736
6878	1845	1.307	326	1.64	.513	.143	.728
6879	2050	1.589	259	1.28	.807	.126	.625
6880	1840	1.319	360	1.80	.496	.153	.743
6881	1770	1.656	362	1.92	.511	.164	.707
6892	1850	1.523	307	1.40	.541	.121	,722
6855	2080	1.719	409	1.62	.542	.149	.705
6856	2080	1.268	237	0.98	.670	.108	.619
6857	1750	1.237	212	.98	.670	.105	.564
6858	1750	1.672	362	1.58	.513	.136	.655
6860	1775	1.488	173	1.01	.664	.105	.556
6861	1770	1.222	326	1.41	.551	.121	.517
6863	2050	1.619	298	1.31	.609	.132	.514
6864	1750	1.223	288	1.42	.762	.128	.440
6865	1750	1.257	314	1.72	.659	.138	.585
6866	2025	1.672	302	1.67	.657	.138	.652
6867	2025	1.254	260	1.34	.739	.120	.655
6868	1850	1.569	258	1.40	.710	.120	.555

No. of Copies Organization	No. of
<u>organization</u>	<u>Copies</u> <u>Organization</u>
12 Commander Defense Technical Info Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	<pre>1 Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Rock Island, IL 61299</pre>
<pre>Director Defense Advanced Research Projects Agency ATTN: LTC. C. Buck 1400 Wilson Boulevard Arlington, VA 22209</pre>	1 Commander US Army Watervliet Arsenal ATTN: Code SARWV-RD, R. Thierry Watervliet, NY 12189 1 Director
2 Director Institute for Defense Analyses ATTN: H. Wolfhard R.T. Oliver	US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL Watervliet, NY 12189
400 Army-Navy Drive Arlington, VA 22202	1 Commander US Army Aviation Research and Development Command
1 Commander US Army Materiel Development and Readiness Command ATTN: DRCDMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333	ATTN: DRDAV-E 4300 Goodfellow Blvd. St. Louis, MO 63120 1 Director US Army Air Mobility Research
6 Commander US Army Armament Research and Development Command	and Development Laboratory Ames Research Center Moffett Field, CA 94035
ATTN: DRDAR-LCA, J. Lannon DRDAR-LCA, D. Downs DRDAR-LCA, L. Harris DRDAR-LC, J.P. Picard DRDAR-LCE, R.F. Walker DRDAR-SCA, L. Stiefel	<pre>1 Commander US Army Communications Rsch and Development Command ATTN: DRDCO-PPA-SA Ft. Monmouth, NJ 07703</pre>
Dover, NJ 07801	1 Commander US Army Electronics Research &
2 Commander US Army Armament Research & Development Command ATTN: DRDAR-TSS Dover, NJ 07801	Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703

No. Copi	-	No. of Copies Organization	
	Commander US Army Missile Command ATTN: DRSMI-R Redstone Arsenal, AL 35809	1 Office of Naval Research ATTN: Code 473 800 N. Quincy Street Arlington, VA 22217	
1	Commander US Army Missile Command ATTN: DRSMI-YDL Redstone Arsenal, AL 35809	1 Commander Naval Sea Systems Command ATTN: J.W. Murrin (NAVSEA-62R2 National Center Building 2, Room 6E08)
1	Commander US Army Natick Research and Development Command ATTN: DRXRE, D. Sieling Natick, MA 01762	Washington, DC 20360 2 Commander Naval Surface Weapons Center ATTN: S.J. Jacobs/Code 240 Code 730	
1	Commander US Army Tank Automotive Rsch and Development Command ATTN: DRDTA-UL Warren, MI 48090	Silver Springs, MD 20910 1 Commander Naval Surface Weapons Center ATTN: Library Br, DX-21 Dahlgren, VA 22448	
1	Commander US Army White Sands Missile Range ATTN: STEWS-DP-AL WSMR, NM 88002	<pre>1 Commander Naval Underwater Systems Center Energy Conversion Department ATTN: R.S. Lasar/Code 5B331</pre>	
1	Commander US Army Materiel & Mechanics Research Center ATTN: DRXMR-ATL Watertown, MA 02172	Newport, RI 02840 2 Commander Naval Weapons Center ATTN: R. Derr C. Thelen	
1	Commander, US Army Research Office ATTN: Tech Lib Research Triangle Park, NC 27706	F. Zarlingo China Lake, CA 93555 1 Commander Naval Research Laboratory	
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL, Tech Lib White Sands Missile Range, NM 88002	ATTN: Code 6180 Washington, DC 20375 2 Superintendent Naval Post Graduate School ATTN: Tech Lib D. Netzer	
		Monterey, CA 93940	

No. of Copies Organization	ion	No. of Copies	
2 Commander Naval Ordnance St ATTN: S. Livanis Tech Lib Indian Head, MD			Calspan Corporation ATTN: E.B. Fisher P.O. Box 400 Buffalo, NY 14211 Chemical Systems Division
3 AFOSR ATTN: L. Caveny B.T. Wolfs Bolling AFB, DC	=		ATTN: D. Altman A. Holtzman P.O. Box 358 Sunnyvale, CA 94088
2 AFRPL (DYSC) ATTN: D. George J.N. Levin Edwards AFB, CA		1	Foster Miller Associates, Inc. ATTN: A.J. Erickson 135 Second Avenue Waltham, MA 02154
<pre>1 Wright Propulsion ATTN: F.D. Stull Wright Patterson,</pre>	/R J T		General Electric Company Armament Department ATTN: M.J. Bulman Lakeside Avenue
<pre>1 National Bureau o ATTN: T. Kashiw Washington, DC</pre>	agi	1	Burlington, VT 05402 General Electric Company
1 Lockheed Palo Alt ATTN: Tech Info 3521 Hanover Stre Palo Alto, CA 9	Ctr et		Flight Propulsion Division ATTN: Tech Lib Cincinnati, OH 45215 Hercules Incorporated
<pre>1 Aerojet Solid Pro ATTN: P. Micheli Sacramento, CA</pre>	-		Alleghany Ballistic Lab ATTN: R. Miller Tech Lib Cumberland, MD 21501
1 Atlantic Research ATTN: M.K. King 5390 Cherokee Ave Alexandria, VA	_	1	IITRI ATTN: M.J. Klein 10 West 35th Street Chicago, IL 60615
1 AVCO Corporation AVCO Everett Rese ATTN: D. Stickle 2385 Revere Beach Everett, MA 021	er Parkway		

No. Copi		No. Copi	
	Olin Corporation Badger Army Ammunition Plant ATTN: J. Ramnarace Baraboo, WI 53913	1	Brigham Young University Dept of Chemical Engineering ATTN: M. W. Beckstead Provo, UT 84601 Provo, UT 84601
-	Olin Corporation New Haven Plant ATTN: R.L. Cook D.W. Riefler 275 Winchester Avenue New Haven, CT 00504	1	California Institute of Tech 204 Karmar Lab ATTN: F.E.C. Culick 1201 E. California Street Pasadena, CA 91125
1	Paul Gough Associates, Inc. ATTN: P.S. Gough P.O. Box 1014 Fortsmouth, NH 03801	1	Case Western Reserve Univ. Division of Aerospace Sciences ATTN: J. Tien Cleveland, OH 44135
1	Physics International Company 2700 Merced Street San Leandro, CA 94577	3	Georgia Institute of Technology School of Aerospace Engineering ATTN: B.T. Zinn E. Price
1	Pulsepower Systems, Inc. ATTX: L.C. Elmore 815 American Street		W.C. Strahle Atlanta, GA 30332
1	San Carlos, CA 94070 Science Applications Inc. 21135 Victory Boulevard Suite 210		Institute of Gas Technology ATTN: D. Gidaspow 3424 S. State Street Chicago, IL 60616
	ATTN: R. Edelman Canoga Park, CA 91303	1	Johns Hopkins University/APL Chemical Propulsion Information Agency
-	United Technologies ATTN: R. Brown Tech Lib F.O. Box 558		ATTN: T. Christian Johns Hopkins Road Laurel, MD 20810
	Sunnyvale, CA 94088	1	Massachusetts Institute of Technology
1	Universal Propulsion Co. ATTN: H.J. McSpadden 1800 W. Deer Valley Rd. Phoenix, AI 85027		Dept of Mechanical Engineering ATTN: T. Toong Cambridge, MD 02139
1	Battelle Memorial Institute ATTN: Tech Lib 505 King Avenue Columbus, OH 45201		

No. Copi		No. o	
1	Pennsylvania State University Applied Research Lab ATTN: G.M. Faeth P.O. Box 30 State College, PA 16801	4	SRI International ATTN: Tech Lib J. Barker D. Crosley D. Golden 333 Ravenswood Avenue
1	Pennsylvania State University Dept of Mechanical Engineering ATTN: K. Kuo University Park, PA 16801	1	Menlo Park, CA 94025 Stevens Institute of Technology Davidson Laboratory ATTN: R. McAlevy, III
1	Pennsylvania State University Dept of Material Sciences ATTN: H. Palmer University Park, PA 16810	1	Hoboken, NJ 07030 University of Illinois Dept of Mechanical Engineering ATTN: H. Krier
1	Princeton University Forrestal Campus ATTN: Tech Lib P.O. Box 710 Princeton, NJ 08540	1	144 MEB, 1206 W. Green Street Urbana, IL 61801 University of Minnesota Dept of Mechanical Engineering
1	Purdue University School of Mechanical Engineerin ATTN: J. Osborn	g 1	ATTN: E. Fletcher Minneapolis, MN 55455 University of Southern California
	TSPC Chaffee Hall West Lafayette, IN 47906		Dept of Chemistry ATTN: S. Benson Los Angeles, CA 90007
		2	University of Texas Dept of Chemistry ATTN: W. Gardiner H. Schaefer Austin, TX 78712
		2	University of Utah Dept of Chemical Engineering ATTN: A. Baer G. Flandro Salt Lake City, UT 84112

No. of Copies

Organization

Aberdeen Proving Ground

Dir, USAMSAA

ATTN: DRXSY-D

DRXSY-MP, H. Cohen

Cdr, USATECOM ATTN: DRSTE-TO-F

Dir, USACSL, Bldg. E3516, EA ATTN: DRDAR-CLB-PA M. Miller

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet, fold as indicated, staple or tape closed, and place in the mail. Your comments will provide us with information for improving future reports.

1. BRL Report Number
2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)
3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.)
4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.
5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.)
6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.
Name:
Telephone Number:
Organization Address: